



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶:

A61F 2/34

A1

(11) International Publication Number:

WO 95/15734

(43) International Publication Date:

15 June 1995 (15.06.95)

(21) International Application Number: PCT/US94/14123

(22) International Filing Date: 8 December 1994 (08.12.94)

(30) Priority Data:

08/165,249

10 December 1993 (10.12.93)

US

(71) Applicant: INTERMEDICS ORTHOPEDICS, INC. [US/US];
1300 E. Anderson Lane, Austin, TX 78752 (US).(72) Inventor: MISER, John, D.; 2910 S. Phoenix Cove, Round
Rock, TX 78664 (US).(74) Agent: ROBINSON, Richard, L.; Sulzermedica USA, Inc.,
4000 Technology Drive, Angleton, TX 77515 (US).(81) Designated States: CA, JP, European patent (AT, BE, CH, DE,
DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).


Published

With international search report.

(54) Title: ACETABULAR SHELL HAVING SCREW HOLES WITH BREAKOUT SEALS

(57) Abstract

An acetabular shell can receive bone screws through screw holes that are initially occluded by an integral seal that can be broken out to render a through hole. The integral seal prevents migration of wear debris from the interior of the shell to the exterior of the shell through an unused screw hole.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

ACETABULAR SHELL HAVING SCREW HOLES WITH BREAKOUT SEALS

Technical Field

The present invention relates generally to implantable prostheses for human joint replacement, and relates more particularly to an acetabular cup for a hip prosthesis.

5

Background Information

A total hip prostheses includes a femoral component and an acetabular cup component. The femoral component has a stem for receipt and fixation within the femoral canal at a resected proximal end of the femur and has a spherical head that may be integral with or removably
10 attached to the stem. The acetabular cup has an outer, generally spherical surface for receipt within a reamed acetabulum and has an inner bearing cavity for receiving the head of the femoral component. The head articulates relative to the bearing cavity such that the total hip prosthesis restores a normal range of motion to an otherwise diseased or damaged hip
15 joint.

One known general configuration for an acetabular cup involves an outer acetabular shell made of a biocompatible metal such as titanium, and a bearing insert made of a biocompatible plastic such as high-density polyethylene. The acetabular shell has a generally hemispherical cup
20 shape, defined by a generally spherical outer surface and a generally spherical inner surface with a shell wall between the inner and outer surfaces. The inner wall defines a generally hemispherical shell cavity having an opening for receipt of the bearing insert. The bearing insert has a generally spherical outer surface dimensioned to be received and fixed
25 within the shell cavity of the acetabular shell, and has a bearing cavity facing outwardly for receipt of the head of the femoral component.

Acetabular shells of such known construction can be affixed to the bone of the patient's acetabulum by bone screws or bone cement. If bone

-2-

screws are selected, the screws are inserted through screw holes in the acetabular shell prior to insertion of the bearing insert into the shell. The shell can also be affixed by a combination of bone screws and bone cement. The acetabular shell will often be provided with a plurality of screw holes in excess of the number of bone screws that would typically be used by the implanting physician, so as to provide a selection of screw sites. Thus, some of the provided screw holes may be used while others are left open, or, in the case where no bone screws are used, all of the screw holes are left open.

Although the bearing insert is usually designed to be received in non-articulating relationship within the acetabular shell, it is believed that a small amount of relative motion between the bearing insert and the acetabular shell nevertheless occurs under the varying load that the acetabular cup is subjected to during use. Such small relative motion, or micro-motion, may result in wear at the interface between the bearing insert and acetabular shell, resulting in the generation of polyethylene or metal debris. It has been suggested that such debris can migrate out of the acetabular cup and come in contact with bone, possibly resulting in osteolysis, which ultimately can lead to bone resorption and possible loosening of the acetabular prosthesis. One apparent pathway for the migration of debris out of the acetabular shell is through open screw holes.

It would be desirable to provide an acetabular shell, designed for use with a bearing insert, that is provided with screw holes for receipt of bone screws, wherein unused screw holes would be occluded to prevent migration through such unused screw holes of wear debris generated within the acetabular shell. This and other desirable features are provided by the present invention.

Disclosure of the Invention

An acetabular shell is provide that can receive bone screws, if desired. Screw holes are provided that are inherently occluded by an integral seal, which seal can be broken out to render the screw hole as a

-3-

through hole for receipt of a bone screw therethrough. If desired, the seal can be left in place if the screw hole is not to be used to receive a bone screw, thereby preventing migration of wear debris from the interior of the acetabular shell to the exterior of the shell through an open, unused screw hole.

In accordance with one aspect of the invention, there is provided a generally hemispherical cup-shaped shell having an inner surface and an outer surface defining a shell wall therebetween. The shell wall has at least one blind hole in the inner surface thereof. The blind hole terminates sufficiently close to the outer surface of the shell to leave a thin seal integral with the shell wall that occludes and separates the blind hole from the exterior of the shell. The seal has at least a portion thereof that is sufficiently thin that the seal can be broken out of the shell wall to render the blind hole as a through hole communicating from the interior to the exterior of the shell.

It is an object of the present invention to provide an acetabular shell that presents the physician with the choice of using bone screws or not to secure the shell in the acetabulum, while providing for occlusion of screw holes that are not selected to receive a bone screw so that migration of wear debris from the interior of the shell to the exterior through open, unused screw holes is prevented.

Other objects and advantages of the present invention will be apparent from the following descriptions of a preferred embodiment with reference to the drawings.

Brief Description of the Drawings

FIG. 1 is a side view of an acetabular shell constructed in accordance with the present invention, shown partially in section.

FIG. 2 is an axial view of the acetabular shell of FIG. 1 looking into the cavity of the acetabular shell.

FIG. 3 is an enlarged cross-section of a portion of the shell wall of the acetabular shell of FIG. 1, showing a section through a screw hole.

-4-

Best Mode for Carrying out the Invention

Referring in particular to FIGS. 1 and 2, there is illustrated an acetabular shell 10 generally shaped as a hemispherical cup defined by an outer hemispherical surface 12 and an inner hemispherical surface 14 having centers that lie on a common axis 16. Inner and outer surfaces 12 and 14 define therebetween a shell wall 18. Preferably, the center 20 of inner surface 14 is offset axially from the center 22 of outer surface 12 such that shell wall 18 is of non-constant thickness. In particular, shell wall 18 is thicker near the apex 24 than near the rim 26.

Shell wall 18, preferably constructed of solid titanium metal, has areas of reduced thickness 28 due to recesses 30 in the outer surface 12. Recesses 30 are filled with a porous titanium coating 32 to a level substantially flush with outer surface 12. The porous coating 32 provides a surface that promotes adhesion of bone cement to acetabular shell 10 and that is capable of promoting and accepting ingrowth of bone therein in non-cemented applications.

An annular groove 34 is located in inner surface 14 proximate rim 26 for the purpose of receiving a corresponding elastically deformable annular protrusion on the outer surface of a polyethylene bearing insert (not shown). Annular groove 34 in cooperation with the annular protrusion of the polyethylene bearing insert serves to axially retain the bearing insert within acetabular shell 10.

A plurality of notches 36 are circumferentially spaced about rim 26 to receive a radial protrusion (not shown) of the polyethylene bearing insert to retain the bearing insert against rotation.

An annular groove 38 having a flat end wall 40 and an annular side wall 42 is located in inner surface 14. Annular groove 38 serves to receive a positioning tool for holding and positioning acetabular shell 10 within the acetabulum during implantation.

A dome hole 44 is centered at the apex 24 in coaxial alignment with axis 16. Dome hole 44 is bounded by a substantially cylindrical side wall 46, a frusto-conical portion 47 extending from said side wall 46 to the inner

-5-

hemispherical surface 14, and a flat end wall 48. Dome hole 44 does not extend through shell wall 18 to the exterior of acetabular shell 10, but rather is closed at one end by end wall 48 and is open at the other end toward the interior of acetabular shell 10. Dome hole 44 receives a corresponding
5 cylindrical protrusion on a polyethylene bearing insert to stabilize the insert against displacement relative to acetabular shell 10. Dome hole 44 can also be employed to receive a positioning tool.

Referring in particular to FIGS. 1 and 3, screw hole 50 is described. In the embodiment illustrated herein, there are preferably two screw holes
10 50 provided in addition to dome hole 44, as is evident in FIG. 2. It should nevertheless be understood that the present invention is also useful in connection with any number of screw holes that may be distributed across acetabular shell 10 to provide the implanting physician with a selection of sites for inserting a bone screw, with the understanding that not all of the
15 screw holes so provided would necessarily be used during any particular implantation. Screw hole 50 is bounded by a substantially cylindrical side wall 52, a spherical surface 54 extending from said side wall 52 to the inner hemispherical surface 14, and a flat end wall 56. Surface 54 is concave toward the interior of acetabular shell 10 and has its center 58 located
20 radially inwardly of inner surface 14. Surface 54 as shown is spherically configured for the purpose of engaging a spherical undersurface of the head of a bone screw. Alternatively, surface 54 could be conically configured for engaging a screw having a head with a conical undersurface. Screw hole 50 does not extend through shell wall 18 to the exterior of
25 acetabular shell 10, but rather is closed at one end by end wall 56 and is open at the other end toward the interior of acetabular shell 10.

As best shown in FIG. 3, cylindrical side wall 52 and flat end wall 56 intersect to define a flat bottomed blind hole that extends almost, but not quite, to a circular intersection with outer hemispherical surface 12. The
30 result is that the portion of shell wall 18 that is partially penetrated by screw hole 50 is quite thin, leaving a thin integral seal 62 that completely occludes screw hole 50 and absolutely prevents passage of wear debris from the

-6-

interior of acetabular shell 10 through screw hole 50, so long as seal 62 remains intact and integral with shell wall 18. It should be noted that screw hole 50 is conveniently formed by machining a flat bottomed cylindrical hole in shell wall 18 from the interior of acetabular shell 10, with the cylindrical hole having a diameter corresponding to cylindrical side wall 52, followed by machining a spherical countersink corresponding to spherical surface 54. The flat bottom of the cylindrical hole is machined to within about 0.010 inch of outer hemispherical surface 12 at the periphery 64 of the flat end wall 56. Because outer hemispherical surface 12 remains spherical where it overlies screw hole 50, seal 62 is thicker at its center than at its edges. Thus, there is formed a screw hole seal 62 that is integral with shell wall 18, but is thinnest at its peripheral circular edge 64 located at the cylindrical side wall 52 of screw hole 50. The thickness of seal 62 at its circular edge is selected, taking into consideration the characteristics of the material of which shell wall 18 is made, such that seal 62 can be broken out of shell wall 18 by application of appropriate force, such as with a punch, to render blind screw hole 50 into a through screw hole for receipt of a bone screw. With titanium as the material of which shell wall 18 is made, it is desirable that the thickness at the circular edge of seal 62 be less than about 0.025 inches. Preferably, the thickness of seal 62 at the circular edge should be about 0.010 inches. If the physician chooses not to select a particular screw hole 50 for receipt of a bone screw, seal 62 is simply left undisturbed to completely occlude that screw hole and eliminate it as a possible path for migration of debris out of acetabular shell 10. Because seal 62 is thicker at its center, it tends to break out cleanly from shell wall 18 at its peripheral circular edge 64 and leave a circular opening aligned with cylindrical side wall 52. Seal 62 is most conveniently made thinner at its edge by machining the bottom of the screw hole flat while leaving the outer surface of the acetabular shell spherical, but other configurations of the screw hole and outer surface of the shell that provide the same result of the seal preferentially breaking out at its edge will be apparent to those of ordinary skill in the art.




-7-

It should also be understood that the foregoing description of the break out seals 62 associated with screw holes 50 applies as well to a break out seal associated with dome hole 44. In addition, the break out seal arrangement as described herein can be used in connection with any
5 hole in an acetabular shell where it is desired to provide the choice of occluding or opening the hole, regardless of the intended purpose of the hole.

While the present invention has been illustrated and described with particularity in terms of a preferred embodiment, it should be understood
10 that no limitation of the scope of the invention is intended thereby. The scope of the invention is defined only by the claims appended hereto. It should also be understood that variations of the particular embodiment described herein incorporating the principles of the present invention will occur to those of ordinary skill in the art and yet be within the scope of the
15 appended claims.

CLAIMS

1. An acetabular shell that can be used with or without bone screws, comprising:
a generally hemispherical cup-shaped shell having an inner surface and an outer surface defining a shell wall therebetween, said shell wall having at
5 least one blind hole in the inner surface thereof, said blind hole terminating sufficiently close to the outer surface of said shell to leave a thin seal integral with said shell wall and occluding and separating said blind hole from the exterior of said shell, the seal having at least a portion thereof that is sufficiently thin that the seal can be broken out of the shell wall to render
10 said blind hole as a through hole communicating from the interior to the exterior of said shell.
2. The acetabular shell of claim 1, wherein said seal is thinnest at its peripheral edge such that said seal tends to break out cleanly and whole at its peripheral edge.
3. The acetabular shell of claim 2, wherein said blind hole has a flat end wall.
4. The acetabular shell of claim 3, wherein said outer surface overlying said blind hole is spherical.
5. The acetabular shell of claim 1, wherein said blind hole is configured to receive a bone screw therethrough after said seal is broken out.
6. The acetabular shell of claim 1, wherein said thin portion of said seal is less than about .025 inches in thickness.
7. The acetabular shell of claim 6, wherein said thin portion of said seal is about 0.010 inches in thickness.
8. The acetabular shell of claim 2, wherein said peripheral edge of said seal is less than about .025 inches in thickness.
9. The acetabular shell of claim 8, wherein said peripheral edge of said seal is about 0.010 inches in thickness.
10. The acetabular shell of claim 1, wherein said blind hole is a machined hole in the shell wall.



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

Internat Application No
PCT/US 94/14123A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61F2/34

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 499 475 (SMITH & NEPHEW RICHARDS INC.) 19 August 1992 see column 9, line 46 - column 10, line 9; claim 24; figure 18 ---	1
A	US,A,4 955 325 (OSTEONICS CORP.) 11 September 1990 see abstract; figure 5 see column 5, line 66 - column 6, line 16 -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

9 March 1995

Date of mailing of the international search report

29. 03. 95

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Steenbakker, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 94/14123

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0499475	19-08-92	US-A- 5226917	13-07-93
		US-A- 5314487	24-05-94
		AU-A- 1090992	20-08-92
		CA-A- 2061183	15-08-92
		JP-A- 5068690	23-03-93
		US-A- 5310408	10-05-94
<hr/>			
US-A-4955325	11-09-90	NONE	
<hr/>			

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.